

Membrane Plates

2-3/8" round, 2" round
 For membrane using #14, #15, K-fast™, Dekspike™, and T.P.R.

- Virgin nylon is resilient and strong, assuring consistent quality and performance.
- Lock-in and anti-rotation features prevent fastener back-out.



- Trilock™ true flat bottom nylon lock plate for installation over dense re-cover boards.



Application

Round 2" Tri-Lock Nylon Plate



- Use with:
- #14 Dekfast
 - #15 Dekfast HS



OD: 2"
 ID: .250"
 Material: Zytel® Nylon

Galvalume Steel Round 2" 20-Ga Barbed Plate



- Use with:
- #14 Dekfast
 - #15 Dekfast HS
 - 1/4" Dekfast Spike
 - TPR



OD: 2"
 ID: .265/.270"
 Thickness: .038"
 Finish: AZ50 Galvalume

Galvalume Steel Round 2-3/8" 20-Ga Barbed Plate

- Use with:
- #14 Dekfast
 - #15 Dekfast HS
 - 1/4" Dekfast Spike
 - TPR
 - K-Fast



OD: 2-3/8"
 ID: .260/.262"
 Thickness: .038"
 Finish: AZ50 Galvalume

Notes

Dimensions are nominal inches unless noted.

Continued on following page

2-3/8" round, 2" round, 3-3/8" round
 For membrane using #14, #15, K-fast™, Dekspike™, Deklite™, and T.P.R.

Membrane Plates

Selection

Item	Part No.	Carton Wt. (lbs)	Carton Qty.	Skid Qty.
Round 2" Tri-Lock Nylon Plate	M3245	16	1000/carton	36,000
Galvalume Steel Round 2", 20-Ga Barbed Plate	M7525	34	1000/pail	40,000
Galvalume Steel Round 2-3/8", 20-Ga Barbed Plate	M7665	35	500/pail	20,000

Approvals

Dekfast fasteners and seam plates are FM approved. Refer to current FM Approval Guide and Supplements for system manufacturers approvals.

Installation

Use in applications approved by the roofing system manufacturer.

Options

