

Purlin Fastener

#3 square drive, drill point
For retro-fit roofing systems where heavy gauge purlin material must be penetrated



- Shank diameter is smaller than that of the drill point and the outside thread diameter, allowing thick metal to be drilled and cleared of chips before threads tap into metal.

- 24 threads per inch allow for easier driving of the fastener and greater pull-out values.

Application

Dekfast #12 Purlin Fasteners
Up to 1/4" purlin steel

- Materials:
- Steel thickness: 18 ga (.045" nominal) through 1/4" (.250")



Head: #3 square, pancake head
Head Height: .110"
Head Dia: .445"
Thread Major Dia: .207"
Shank Dia: .179" nom

Strength (lbs ult.):
Tensile: 2300
Torsional: 100 in-lbs min

Pull-out: (lbs avg.):
18 ga (.045): 375
16 ga (.060): 599
14 ga (.075): 869
12 ga (.104): 1477
3/16" (.188): 2300*
1/4" (.250): 2300*

Notes

Dimensions are nominal inches unless noted.
*Denotes tensile failure of fastener (fastener failed in tensile before pulling out of tabulated substrate). Fasteners are designed for the attachment of roofing materials to purlins. Designated holding values depend on the quality of materials to which the fastener is being anchored. Pull-out tests need to be conducted to verify that the substrate provides adequate pull-out values.

Selection

Length	Part No.	Composite Thickness	Carton Wt. (lbs)	Carton Qty.
12 x 3-3/4"	C4325-999B	Up to 2-3/4"	34	1000
12 x 4-3/4"	C4335-999B	1-1/4" to 3-3/4"	40	1000
12 x 5-3/4"	C4345-999B	2-1/4" to 4-3/4"	48	1000
12 x 6-3/4"	C4355-999B	3-1/4" to 5 3/4"	54	1000
12 x 7-3/4"	C4365-999B	4-1/4" to 6-3/4"	62	1000

Approvals

Dekfast purlin fasteners coating exceeds Factory Mutual corrosion resistance Standard 4470.

Installation

Tools: 1800 – 2500 rpm screw gun equipped with depth-sensing nosepiece.

Options

